



EURO SIZE PALLET [05] 05-HD







Euro pallet with integrated reinforcement proven its worth in internal logistic processes of numerous other industries. Its external standard dimensions make it the perfect basis for hygienically flawless stackable containers and also suitable for worldwide exports.

TECHNICAL DATA

Pallet Name	Heavy Duty			
Dimensions LxWxH (mm)	1200 x 800 x 150			
Steel Enforcement	Without	With		
CODE	05-HD	05-HD/S		
Static Loading (kg)	4000	5000		
Dynamic Loading (kg)	2000	3000		
Racking Loading (kg)	1000	1500		
Structure	I.			
Runners	3 longitudinal, 3 transverse			
Standard Color	(•		
Container Load [40' HC]	408 PCs			
Standard Truck Load	660 PCs			
Rackable	1			

AVAILABLE WITH

Safety Lips	✓
Caps	A
Anti-Slip Rubber	×
Client LOGO Printed	✓

OPTIONS ON REQUEST

Steel enforcement	*
Client LOGO Engraved	4
RFID	*
Customized Color	*
Fire Retardant	*

ADVANTAGES

- Anti-impact perimeter
- Large window operations for easy handling
- Plastic pallets have fewer or no repairs.
- Plastic pallets improve efficiencies due to standard dimensions and lack of broken board.
- Plastic pallets offer better product protection no nails or broken boards to damage payload.
- Plastic pallets offer better stability no damaged or missing boards causing spills or falling stacks.
- Plastic pallets improve safety and lower workers compensation claims.
- Plastic pallets allow for greater utilization of warehouse space stability and higher stacking.

Recommendations for use

- Do not stack more than 30 pallets, which is equivalent to a height of 4.65 m when empty.
- Once stacked in height check that they are properly fitted.

- Due to the characteristics of plastic materials and manufacturing process, the dimensions and the weight of the pallets may present certain tolerances.

The specification can be affected in case of alteration of the product with parts and / or materials different from those approved by the RePall quality department.
RePall reserves the right to modify any information herein indicated without prior notice.

- Any warranty, specification or liability on the part of RePall will be terminated in case of modification of the product with spare parts not supplied by RePall.



⁻ The values indicated are approximate and are based on practical experience and ISO 8611-1, evenly distributed load over pallet surface, at ambient temperature (23° C) for a specific time. Different load conditions produce different values that have to be checked at the customer's request. Any deterioration or breakage in the pallet may vary these results.