

PETROCHEMICAL PALLET (Export)


140x110x15 cm

09-EX



High quality plastic pallets with special dimensions (140X110X15 cm), 09-EX pallet having ideal size containing mesh type surface and anti-slip rubbers for the safe and efficient handling of bulk bags, super sacks. Especially designed for export shipments in the Petrochemical Industry.

TECHNICAL DATA

CODE	09-EX
Dimensions LxWxH (cm)	140x110x15
Static Loading (kg)	5000
Dynamic Loading (kg)	1500
Racking Loading (kg)	400
Structure	
Runners	3 longitudinal, 3 transverse
Standard Color	●
Container Load [40' HC]	288 PCs
Standard Truck Load	440 PCs
Rackable	✓

AVAILABLE WITH

Client LOGO Printed



Anti-slip Rubber



OPTIONS ON REQUEST

Customized Color



Client LOGO Engraved



RFID



Fire Retardant



ADVANTAGES

- ✓ Anti-impact perimeter
- ✓ Large window operations for easy handling
- ✓ Plastic pallets have fewer or no repairs.
- ✓ Plastic pallets improve efficiencies due to standard dimensions and lack of broken board.
- ✓ Plastic pallets offer better product protection no nails or broken boards to damage payload.
- ✓ Plastic pallets offer better stability no damaged or missing boards causing spills or falling stacks.
- ✓ Plastic pallets improve safety and lower workers compensation claims.
- ✓ Plastic pallets allow for greater utilization of warehouse space stability and higher stacking.

Recommendations for use

- ✓ Do not stack more than 30 pallets, which is equivalent to a height of 4.65 m when empty.
- ✓ Once stacked in height check that they are properly fitted.

- The values indicated are approximate and are based on practical experience and ISO 86111-, evenly distributed load over pallet surface, at ambient temperature (23 °C) for a specific time. Different load conditions produce different values that have to be checked at the customer's request. Any deterioration or breakage in the pallet may vary these results.
- Due to the characteristics of plastic materials and manufacturing process, the dimensions and the weight of the pallets may present certain tolerances.
- The specification can be affected in case of alteration of the product with parts and / or materials different from those approved by the RePal quality department.
- RePal reserves the right to modify any information herein indicated without prior notice.
- Any warranty, specification or liability on the part of RePal will be terminated in case of modification of the product with spare parts not supplied by RePal.