



SPILL PALLET [11]

SP-11



4 Drum Polyethylene Spill Pallet: A containment sump with deck surface used for storing and containing any leaks, spills or drips from intermediate bulk containers.

Advantages:

- 30 cm high - lower profile for easier access dispensing.
- Polyethylene construction, chemical-resistant, won't rust or corrode.
- 4-way forklift entry for easy movement when not loaded.
- Available with drain.

TECHNICAL DATA

Pallet Name	Spill Pallet
Dimensions LxWxH (mm)	1320 x 1320 x 300
CODE	SP-11
Static Loading (kg)	3000
Dynamic Loading (kg)	1500
Structure	■ ■ ■
Runners	N/A
Standard Color	●
Container Load [40' HC]	280 PCs
Standard Truck Load	280 PCs

AVAILABLE WITH

Safety Lips	✗
Caps	✗
Anti-Slip Rubber	✓
Client LOGO Printed	✓

OPTIONS ON REQUEST

Steel enforcement	✗
Client LOGO Engraved	✓
RFID	✗
Customized Color	✓
Fire Retardant	✓

ADVANTAGES

- ✓ Anti-impact perimeter
- ✓ Large window operations for easy handling
- ✓ Plastic pallets have fewer or no repairs.
- ✓ Plastic pallets improve efficiencies due to standard dimensions and lack of broken board.
- ✓ Plastic pallets offer better product protection no nails or broken boards to damage payload.
- ✓ Plastic pallets offer better stability no damaged or missing boards causing spills or falling stacks.
- ✓ Plastic pallets improve safety and lower workers compensation claims.
- ✓ Plastic pallets allow for greater utilization of warehouse space stability and higher stacking.

Recommendations for use

- ✓ Do not stack more than 30 pallets, which is equivalent to a height of 4.65 m when empty.
- ✓ Once stacked in height check that they are properly fitted.

- The values indicated are approximate and are based on practical experience and ISO 8611-1, evenly distributed load over pallet surface, at ambient temperature (23° C) for a specific time. Different load conditions produce different values that have to be checked at the customer's request. Any deterioration or breakage in the pallet may vary these results.
- Due to the characteristics of plastic materials and manufacturing process, the dimensions and the weight of the pallets may present certain tolerances.
- The specification can be affected in case of alteration of the product with parts and / or materials different from those approved by the RePall quality department.
- RePall reserves the right to modify any information herein indicated without prior notice.
- Any warranty, specification or liability on the part of RePall will be terminated in case of modification of the product with spare parts not supplied by RePall.

